

EXITING — EGRESS

HAZARD	Satisfactory	Needs Attention	Target Date of Correction	Date Corrected
Are all exits marked with an exit sign and illuminated by a reliable light source?				
Are the directions to exits, when not immediately apparent, marked with visible signs?				
Are doors, or passageways, that are neither exits nor access to exits and which could be mistaken for exits, appropriately marked " NOT AN EXIT ", " TO BASEMENT ", " STOREROOM ", etc.?				
Are exit signs provided with the word " EXIT " in lettering at least 5" high and the stroke of the lettering at least ½" wide?				
Are exit doors side-hinged?				
Are all exits kept free of obstructions?				
Are at least 2 means of exit provided from elevated platforms, or rooms where the absence of a 2nd exit would increase the risk of injury from corrosive, flammable, or explosive substances?				
Are there sufficient exits to permit prompt escape in case of emergency?				
Are special precautions taken to protect employees during construction and repair operations?				
Are the number of exits from each floor of a building and the number of exits from the building itself, appropriate for the building occupancy load?				
Are exit stairways, which are required to be separated from other parts of a building, enclosed by at least one-hour fire-resistant construction?				
When ramps are used as part of required exiting from a building, is the ramp slope limited to 1 ft. vertical and 12 ft. horizontal?				
Where exiting will be through frameless glass doors, glass exit doors, storm doors and such, are the doors fully tempered and meeting safety requirements for human impact?				

Name _____	Date _____
------------	------------